




HAMBURG INDUSTRIES CO., LTD.

6F., No. 12, Ln. 270, Sec. 3, Beishen Rd., Shenkeng Dist., New Taipei City 222, Taiwan



TECHNICAL CHARACTERISTICS

1. General Characteristics

Dimensions: 11.10L x 7.60W x 1.50H mm
11.10L x 7.60W x 1.80H mm
11.10L x 7.60W x 2.00H mm
11.10L x 7.60W x 2.40H mm
11.10L x 7.60W x 2.60H mm

Weight: Approx. 0.2 g

Contact principle: Friction technology

Operating position: Shaft up / Down / Horizontal

Mounting System: SMT Type (without post)

Durability: 10,000 cycles min.

2. Mechanical Characteristics

Insulation material: Thermoplastic, UL 94V-0
RoHS Directive 2011/65/EU Compliant

3. Electrical Characteristics

Number of contacts: 6 pins

Contact resistance: 50 mΩ typical, 100 mΩ max.

Insulation resistance: >1000 MΩ / 500 VDC

4. Solderability

Wave: Not applicable

IR reflow: 260°C, 10 sec. Max.

Manual soldering: 360°C, 3 sec. Max.


5. Environmental Characteristics

Operating temperature: - 40°C ~ + 85°C

Operating humidity: 10 % ~ 95 % RH

Storage temperature: - 40°C ~ + 85°C


Storage humidity: 10 % ~ 95 % RH



Recommend card slot height: 1.0 mm

Unit: mm; Tolerances: ±0.15 mm

Mechanical outline dimension



Unit: mm; Tolerances: ±0.05 mm

Reference dimension for PCB layout

H&V Smart Card Connector

Model No.: ICC-409

Revision: 2.0

Date: MAY 01, 2014

Note:

1. Coplanarity of solder pins 0.10mm max.

2. Recommended thickness of solder paste > 0.15mm.

For further information, please contact:

Tel: +886 2 2662 8882(Rep.) Fax: +886 2 2662 7201~2 E-mail: taipei@hamburg.com.tw URL: <http://www.hamburg.com.tw>